



niveo
P R O F E S S I O N A L



NGS16MCR

(16-slot Media Converter Chassis for Redundant Power Supply)

More information:
WWW.NIVEOPROFESSIONAL.COM
INFO@NIVEOPROFESSIONAL.COM



Key Features

- Up to 16 slots of Media Converters
- 19” standard rack-mount size and 3U height
- Hot-swappable replacement of Media Converters and power supplies
- Two redundant power supplies with two cooling fans
- Power isolation design to ensure each bay is electrically isolated from others

Specifications

Capacity	16 bays for up to 16 Media Converters
Power	One hot-swappable power supply Optional second hot-swappable power supply Input: 48V DC
Cooling	Two internal cooling fans
Dimensions	130 x 440 x 300 mm (H x W x D)
Operating Temperature	0 to 40°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE
NGS16MCR-PS, Input 48V DC Media Converter Chassis Power Supply	
Dimensions	90 x 150 x 180 mm (H x W x D)
Operating Temperature	0 to 50°C
Storage Temperature	-20 to 70°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE