



## NGS-IPV16/NGS-IPV24

(16/ 24 Rear Port Managed Video-over-IP-Switch)

**More information:**

**[WWW.NIVEOPROFESSIONAL.COM](http://WWW.NIVEOPROFESSIONAL.COM)**

**[INFO@NIVEOPROFESSIONAL.COM](mailto:INFO@NIVEOPROFESSIONAL.COM)**



# Product Specification

## Zero Config Video over IP

The NGS-IPV16/24 are designed to make any Video-Over-IP project as simple as can be. Simply unpack, plug in and go! Power most standard POE+ encoders and decoders. The built-in remote management software allows for easy access and monitoring of both switch and encoders / decoders. The switch supports most 1-Gigabit based video-over-IP systems

## 2 Gigabit SFP Open Slots

The NGS-IPV16/24 is a 18/ 26-port design. It supports 2 additional SFP open slots to uplink to servers, storage, or other switching devices for long loop reach applications. The 2 SFP slots can support different types, speed and distance SFP transceivers. It also supports legacy 100M SFP transceiver. If the 100M fiber infrastructure is constructed and 100M bandwidth is enough, the 100M SFP transceiver can be an optional choice for the legacy 100M network environment.

## Additional Full Layer 2/3 Management Features

For advanced set ups, installers have access to the switches full Layer 2+ Management features. The software set includes up to 4K 802.1Q VLAN and advanced Protocol VLAN, Private VLAN, MVR... advanced VLAN features. There are 8 physical queues Quality of Service, IPv4/v6 Multicast filtering, Rapid Spanning Tree protocol to avoid network loop, Multiple Spanning Tree Protocol to integrate VLAN and Spanning Tree, LACP, LLDP; sFlow, port mirroring, cable diagnostic and advanced Network Security features. It also provides Console CLI for out of band management and SNMP, Web GUI for in band Management.

## Advanced Security

The switch supports advanced security features. For switch management, there are secured HTTPS and SSH, the login password, configuration packets are secured. The port binding allows to bind specific MAC address to the port, only the MAC has the privilege to access the network. The 802.1X port based Access Control, every user should be authorized first when they want to access the network. AAA is the short of the Authentication, Authorization and Accounting with RADIUS, TACAS+ server. Layer 2+ Access Control List allows user to define the access privilege based on IP, MAC, Port number... etc.



# Specifications

<b>Standards</b>	Ethernet: IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3az EEE PoE: IEEE 802.3at PoE+ Protocol: IEEE 802.3x - Flow Control, IEEE 802.1Q – VLAN, IEEE 802.1p - Class of Service, IEEE 802.1D - Spanning Tree, IEEE 802.1w - Rapid Spanning Tree, IEEE 802.1s - Multiple Spanning Tree, IEEE 802.3ad - Link Aggregation Control Protocol (LACP), IEEE802.1v - Protocol VLAN, IEEE 802.1AB - LLDP (Link Layer Discovery Protocol), IEEE 802.1X - Access Control
<b>Interface</b>	Number of Port: 26 10/100/1000Base RJ-45 Port: 24, Auto-negotiation, Auto MDI/MDIX 100/1000Base-X SFP: 2
<b>Performance</b>	Switch Fabric:32/ 52Gbps MAC Address Table Size: 8K Forwarding Rate: 26.838.7Mpps Packet Buffer: 4Mb
<b>PoE Features</b>	<b>802.3af/at Compliant</b> <b>Max. Power Output Per Port:</b> 30W <b>Power Consumption :</b> 310W Current Sharing <b>PoE Management:</b> Enable/Disable per-port Priority Setting per-port Maximum Power per-port/system PoE Mode Setting per-port PD Classification, PoE Status
<b>L2 Features</b>	<b>Flow Control:</b> 802.3x (Full-duplex)ort/ Back-Pressure (Half-duplex) <b>Spanning Tree:</b> IEEE 802.1D-2004(Includes IEEE 802.1w): Rapid Spanning Tree Protocol 802.1s Multiple Spanning Tree Protocol <b>Loop Detection</b>  <b>VLAN:</b> IEEE 802.1Q Tagged Based, Max. VLAN Group: 4K QinQ Port-based VLAN Voice VLAN Private VLAN MVR MAC-Based VLAN Protocol-Based VAN <b>Link Aggregation:</b> Static Trunk & IEEE 802.3ad with LACP Max. Group: 13



	<p>Max. Ports/Group: 16</p> <p><b>IGMP Snooping:</b></p> <ul style="list-style-type: none"><li>IGMP Snooping v1/v2/v3</li><li>IPv6 MLD Snooping v1/v2</li><li>Querier support/ IGMP Filtering, IGMP Leave Proxy, Immediate Leave</li></ul> <p><b>Storm Control:</b> Broadcast/ Multi-cast/ Un-known Unicast</p> <p><b>Jumbo Frame Support:</b> 9K</p>
<b>QoS Features</b>	<p><b>Number of Priority queue:</b> 8 queues/ port</p> <p><b>Scheduling for priority queue :</b> WRR/Strict Priority scheduling/Hybrid</p> <p><b>CoS :</b></p> <ul style="list-style-type: none"><li>802.1p/ IP Precedence/ IP TOS Precedence</li><li>IP DSCP/ Port based Priority</li></ul> <p><b>Rate Limiting:</b> Ingress/Egress: 1Kbps/ 1pps granularity</p> <p><b>DiffServ (RFC2474) remarking</b></p>
<b>Security</b>	<p><b>User Name / Password Protection</b></p> <p><b>User Privilege:</b> up to 15 levels</p> <p><b>IEEE 802.1x:</b> Port-based Access Control</p> <p><b>IP Source Guard</b></p> <p><b>MAC Based Authentication</b></p> <p><b>Web-based Authentication</b></p> <p><b>HTTPS</b></p> <p><b>SSHv2</b></p> <p><b>RADIUS:</b> Authentication/ Accounting</p> <p><b>TACACS+:</b> Authentication</p> <p><b>ACL (Access control list)</b></p>
<b>Management</b>	<p><b>Command Line Interface (CLI)</b></p> <p><b>Web Based Management</b></p> <p><b>Telnet</b></p> <p><b>Access Management Filtering:</b> SNMP/WEB/SSH/TELNET</p> <p><b>SNMP:</b> v1/v2c/v3</p> <p><b>RMON:</b> RMON (1,2,3, &amp; 9 groups)</p> <p><b>DHCP:</b> Client/ Relay/ Option82/ Snooping</p> <p><b>Event/Error Log</b></p> <p><b>Software Download/ Upgrade:</b> HTTP</p> <p><b>Configuration Download / Upload</b></p> <p><b>sFlow</b></p> <p><b>Port Mirroring:</b> One to One/ Many to One</p> <p><b>Remote Ping</b></p> <p><b>NTP/LLDP</b></p> <p><b>UPnP</b></p> <p><b>EEE Configuration</b></p> <p><b>Cable Diagnostics</b></p> <p><b>IPv6 Configuration</b></p>
<b>Power Input</b>	100~240VAC



<b>Power Consumption</b>	PoE: max. 500W System: max. 21.5W
<b>Mechanical</b>	<b>Dimension(H*W*D)</b> : 45*440*330mm / 1.77*17.32*12.99 inch <b>Weight</b> : 4.7 kg / 10.36 lbs
<b>Operating Temperature</b>	0~40°C/32~104 °F
<b>Humidity</b>	5~90% (non-condensing)
<b>Certifications</b>	FCC Class A, CE, c-UL-us (Q4-2013)