



NRS6GP

(4 Port PoE gigabit Switch with 1-Port SFP & 1 Gb Uplink Port)

More information:

WWW.NIVEOPROFESSIONAL.COM

INFO@NIVEOPROFESSIONAL.COM



Product Specification

The NRS6GP provides 5 Gigabit ports combined with a 1 SFP port, making it the ideal device for small commercial and residential integrations. Offering PoE+ for powering a wide array of devices, the rock solid fanless design is built to last in every modern installation.

Technical Specifications

Model No.	NRS6GP
I/O ports	1*10/100/1000Mbps RJ-45 port 4*10/100/1000Mbps PoE +RJ-45 ports 1* SFP port
Standard	IEEE 802.3 10Base T Ethernet IEEE 802.3u 100Base TX(Fast Ethernet) IEEE 802.3ab 1000Base T(Gigabit Ethernet) IEEE 802.3z 1000base SX LX IEEE 802.3x Flow control IEEE 802.3af Power over Ethernet/PSE IEEE 802.3at Power over Ethernet Plus/PSE
LED Define	PWR <ul style="list-style-type: none">• Green: Power is on• Not illuminated: Power is off LAN/Uplink port <ul style="list-style-type: none">• Green(Solid): indicate the port isoperating at 1000 Mbps• Green(Blinking): indicate the activity is occurring• Orange(Solid): indicate the port is operating at 10/100 Mbps• Orange(Blinking): indicate the activity is occurring PoE interfaces• Orange: PoE in Use SFP interfaces <ul style="list-style-type: none">• Green: SFP is linking
MAC table	2K
Buffer Memory	128KB
PoE Budget	65W
Jumbo Frame	9k bytes
Switching Fabric	12Gbps
Power Input	External UL certified power supply: 100-240VAC, 50/60Hz 55v DC, 1.3A



Dimension	147(L)*106(W)*28(H)mm
FAN Design	Fan-less
Temperature	Operating: 0°C~40°C Storage : -20°C~70°C
Humidity	10%~90% RH(non-condensing)
Safety	LVD EN60950-1: 2011+A2: 2013
EMC	FCC Part 15,Subpart B:ANSI C63.4-2014 (Class B) CE EN55032: 2015+AC:2020 EN55035: 2017+A11:2020